Make Sensing Matter







Tel: +86-592-5922772(8801) - Sales +86-592-5922772(8701) - Support Mail: sales@milesight.com support@milesight.com Address: Building C09, Software Park Phase III, Xiamen 361024, Fujian, China






PRODUCT CATALOG

Milesight Multi-potential **Sensing Products**



WHY Milesight? Because We Make Sensing Matter





Capturing Meaningful Data Matters

We provide multi-potential sensing products, focusing on the data that adds value, reflects patterns, and assists decision-making.



Responding to Customer Demands Matters

We adapt to evolving customer needs, creating products that are relevant to them and making a significant impact across varied applications, projects, and industries.



Thriving Together with Partners Matters

Alongside our expanding partner ecosystem, we develop comprehensive solutions, deliver value offerings, and accelerate results for customers.

INTELLIGENCE - AI Empowers Security







Object Counting







Face Detection Fire Smoke Detection Hard Hat Detection Intrusion Detection

Al Video Analytics

IMAGE - Embrace Sharper Vison Even at Night





High-quality Deblur



P-Iris Control



Comprehensive Defogging



SONY STARVIS 2.0



Corridor Mode

EIS Electronic Image Stabilization

Two Colors Available microSD/SDHC/SDXC Card Slot Reset Button DC 12V Smoked Dome Cover Alarm I/O & Audio Out & DC 12V Ethernet Port (PoE) Cable Management Built-in Microphone Water-proof Connector Clamshell Design

INTEROPERABILITY - Extensive Compatibility

(Milesight Al Motorized Pro Dome Camera)

Various Protocols Supported

IPv4/IPv6, SIP, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, PPPoE. VLAN. 802.1x. OoS. IGMP. ICMP. SSL

ONVIF Profile G/M/S/T

Easy to be integrated into security systems on the basis of the ONVIF protocols by supporting ONVIF profile G/M/S/T.




Milesight Video Surveillance Software

Integrated and simplified video management, covering device connectivity, remote management, data analysis, and decision-making.



SIP / VoIP

Integrate Milesight Network Cameras with SIP protocol into VoIP systems for a secure, cost-effective, and easily managed solution, enabling features like alarm push notifications and live camera views via mobile apps or VoIP telephones.



Third-party Compatibility

Offer more flexibility to users by deepening communication with different security system through CGI / API.



AI MINI SERIES



Small in Size, Big on Intelligence

Introducing Milesight compact yet powerful entry-level mini cameras. With sleek design and advanced features, they offer exceptional performance. Capture clear and detailed footage with high-resolution image quality and versatile functionality. Perfect for home monitoring and small-scale installations, our mini cameras provide reliable surveillance solutions.











Inimitable Mini Bullet

Clamshell Design

Revolutionary IR Performance

Point-contact Power Supply

Al Motorized Dome Camera

- 2/5/8 MP
- · Motorized Zoom Lens
- 60fps High Frame Rate
- 120dB Super WDR
- 50m IR Distance
- Built-in Microphone Audio I/O, Alarm I/O, PoE & DC 12V
- · Integrated Junction Box



Al Motorized Bullet Camera

- 2/5/8 MP
- Motorized Zoom Lens • 90fps High Frame Rate
- 140dB Super WDR
- 50m IR Distance
- Audio I/O, Alarm I/O, PoE & DC 12V
- · Integrated Junction Box



Al Vandal-proof Mini Dome Camera

- 2/5/8 MP
- 60fps High Frame Rate
- 120dB Super WDR
- 30m IR Distance
- Built-in Microphone Audio I/O,
- Alarm I/O, PoE & DC 12V
- 2/5/8 MP • 60fps High Frame Rate 120dB Super WDR
 - 0.005Lux Starlight

Al Vandal-proof

Mini Bullet Camera

- 30m IR Distance
- · Point-contact Power Supply · Integrated Junction Box
- · Reliable Anti-vibration Performance



Al Weather-proof Mini Dome Camera

- 2/5/8 MP
- · 60fps High Frame Rate
- 120dB Super WDR
- 25m IR Distance
- · Built-in Microphone
- Clamshell Design
- · Recessed Installation
- · Integrated Junction Box



Al Weather-proof Mini **Bullet Camera**

- 2/5/8 MP
- 60fps High Frame Rate
- 140dB Super WDR
- 0.005Lux Starlight
- 50m IR Distance
- · Audio I/O, Alarm I/O,
- PoE & DC 12V · Unique Sunshield Design



Al IR Mini Dome Camera

- 2/5/8 MP
- 60fps High Frame Rate
- 120dB Super WDR
- 0.005Lux Starlight
- 20m IR Distance
- Built-in Microphone

· Recessed Installation

- Ultra-mini Size
- · Screw-free Design

F1.0 Aperture

• Up to 30m Illuminator Distance · 3-Axis Mechanical Design

Al Color⁺ Vandal-proof

• Full-color Image Performance

Amazing Image Effect with

• 0.001 Lux Ultra Low-light

Mini Bullet Camera

• 2/5/8 MP

- Point-contact Power Supply

AI NETWORK CAMERA

AI NETWORK CAMERA

AI PRO SERIES



Precision Perfected. Pro Excellence Embodied

With advanced features and enhanced capabilities, Milesight Pro Series cameras redefine excellence. Experience extended infrared distance, a wide range of interface options and a wide choice of lenses for ultimate flexibility. With superior performance and cutting-edge technology, Milesight Pro cameras deliver exceptional image quality that accurately captures every detail. Whether it's for large-scale surveillance projects or specialised applications, you can rely on the Milesight Pro Series to meet the needs of professionals who demand the highest levels of performance and versatility.









Recessed Installation



Efficient & Simple Installation



AI 4X/12X Pro Bullet Plus Camera

- 2/4/5/8 MP
- 1/1.8" STARVIS Starlight Sensor
- 4X/12X Optical Zoom
- 90fps High Frame Rate
- Smart IR II with 180m IR Distance · Integrated Junction Box
- 140dB Super WDR

- · Robust Structural Design & Advanced AI Capabilities
- Integrated Junction Box




Al Motorized Pro Bullet Plus Camera

- 2/4/5/8 MP
- 1/1.8" STARVIS Starlight Sensor
- Motorized Zoom Lens
- 90fps High Frame Rate
- 140dB Super WDR
- Smart IR II with 100m IR Distance



Al Motorized Pro Bullet Camera

- 1/1.8" STARVIS Starlight Sensor
- Motorized Zoom Lens
- · 90fps High Frame Rate



Al Motorized Pro Dome Camera

- 2/4/5/8 MP
- 1/1.8" STARVIS Starlight Sensor
- Motorized Zoom Lens
- · 90fps High Frame Rate
- 140dB Super WDR
- · Smart IR II with 90m IR Distance
- · Recessed Installation
- Clamshell Design
- Smoked Dome Cover



Al Pro Box Plus Camera

- 2/4/5/8 MP
- Various Zoom Lens Supported
- 0.001Lux Ultra Low-light
- 60fps High Frame Rate
- 140dB Super WDR
- Audio I/O, Alarm I/O, PoE & DC 12V
- · Protective Housing (Optional)

AIPTZ SERIES



Intelligent PTZ to Transform Your World

Milesight PTZ cameras revolutionize versatility and control. With the ability to pan, tilt and zoom, Milesight cameras offer precise navigation and focus on areas of interest. Experience high-resolution imaging, powerful zoom capabilities, and intelligent tracking for exceptional surveillance performance. Perfect for large-scale installations, public safety, or critical infrastructure, Milesight PTZ cameras provide flexibility and control to capture every detail





PTZ Privacy Mask



IR Anti-reflection Design



PTZ Auto Tracking



3D Positioning & Keyboard Control



AI 12X PTZ Bullet Camera

- 2/5 MP
- 140dB Super WDR
- 90fps High Frame Rate
- 360° Endless Pan & 75° Tilt · Smart IR II with 140m IR Distance
- PTZ Auto Tracking

- · Intelligent White LED Audio I/O, Alarm I/O, PoE & DC 12V



Pedestal Mount

Wall Mount

Al 12X/20X/23X PTZ Bullet Plus Camera

- 2/4/5/8 MP
- 0.002Lux @ 1/1.8" STARVIS Sensor
- 140dB Super WDR
- 90fps High Frame Rate
- 360°Endless Pan & 75°Tilt
- · Smart IR II with 180m IR Distance
- PTZ Auto Tracking • Audio I/O, Alarm I/O, PoE & DC 12V
- New-generation PTZ Motor
- High Horizontal Accuracy: <0.5 Degrees • High Vertical Accuracy: 0.3~0.5 Degrees

Al 12X/20X/23X PTZ Dome Camera

- 2/4/5 MP
- 0.002Lux @ 1/1.8" STARVIS Sensor
- 140dB Super WDR
- 90fps High Frame Rate 360°Endless Pan & 95°Auto-flip Tilt
- · Pan Speed 450°/s, Tilt Speed 360°/s
- Smart IR II with 160m IR Distance PTZ Auto Tracking
- Audio I/O, Alarm I/O, PoE & DC 12V • IR Anti-reflection Design
- · Recessed Installation



AI 25X/30X/36X/42X Speed Dome

- 2/4/5/8 MP
- 0.002Lux @1/1.8" STARVIS Sensor
- 100fps High Frame Rate • 360°Endless Pan & 95°Auto-flip Tilt
- · High Horizontal Accuracy: 0.1 Degrees
- Pan Speed 400°/s, Tilt Speed 320°/s
- Smart IR II with 200/300m IR Distance
- Audio I/O. 4*Alarm In. 2*Alarm Out. PoE & AC 24V
- Smart Rain-sensing Wiper (Optional)

AI NETWORK CAMERA

Boundless World, Truly Within Reach

Milesight Panorama Series cameras revolutionise the way you see the world. Capture complete 180/360-degree panoramic views with advanced technology, revealing every detail and eliminating blind spots. Ideal for surveillance, virtual tours, or capturing breathtaking landscapes, these cameras offer unparalleled performance and versatility. Elevate your visual exploration with Milesight Panoramic Series.







Stunning Dewarping Ability

AI PANORAMIC SERIES





People Flow Analytics







Delicate & Exquisite Design

Various Accessories For Easy Installation

Al 360° Panoramic Fisheye Camera

- 4K/12MP
- 1/1.8" Sony STARVIS 2 Sensor
- On-board/Client-side Dewarping
- Fisheye Auto Tracking
- Advanced Heat Map
- Smart IR II with 15m IR Distance
- · Built-in Microphone, Audio I/O,
- Alarm I/O, PoE & DC 12V
- · Screw-free Design Ceiling Mount/Wall Mount/Flat Mount



Al 180° Panoramic Mini Bullet Camera

- 5MP/4K
- Advanced Heat Map
- 180° IR Coverage
- · New Generation Panoramic IR Technology
- Smart IR II with 15m IR Distance
- Ultra Mini Size -
- 95.8mmX74mmX158.5mm · Built-in Microphone



Al 180° Panoramic Mini Dome Camera

- 5MP/4K
 - Advanced Heat Map
 - 180° IR Coverage
 - · New Generation Panoramic IR Technology
 - Smart IR II with 15m IR Distance
 - · Built-in Microphone
 - Integrated Junction Box



Al Dual-sensor 180° Panoramic Camera

- Exceptional 2*4MP Image Intelligent Analytics Integration
- 180° Stitched Panoramas
- · Wide-Angle Perspective
- · Seamless Dual-View Monitoring Smart IR II with 30m IR Distance
- · Built-in Microphone · Ceiling Mount / Wall Mount

NVR

Thermal Design

Recorded Data

Transmits Back

ANR



Output 1

*NVR CANNOT connect to VMS/CMS/APP



Multi-address Load Balance Net Fault-tolerance

IP1 (Main) IP1 (Backup)

RAID

Output 2

N+1 Hot Spare

4K Pro NVR

8000 Series

AI 5G SERIES



















ONVIFIGMST AT AT | FIP67 | \$\frac{1}{2}\tag{1} \text{ IK10} | 56 \text{ 5G} | \text{ OT IOT

Empower the Future of Smart Connectivity

Milesight takes security to the next level by combining AI deep learning



5G High Mobility Embedded AloT Technology

with cutting-edge 5G and IoT technology in the 5G AIoT Camera. This powerful hybrid solution provides seamless remote video surveillance with high-definition feeds and minimal latency. By aggregating video

insights and data from IoT devices, it enables situational awareness and delivers analytics-driven insights. Experience the future of security with Milesight's 5G AloT Camera, where advanced technologies 4K H.265 Mini NVR converge for unparalleled performance.

1000 Series

- 4/8-CH Network Video Input
- Up to 10TB Storage & NAS
- 4K Decoding Capabilities
- Dual Stream Recording
- AI VCA Management & POS Integration
- Thermal Design
- ANR



CLOSE-LOOP VIDEO MANAGEMENT

4K H.265 Pro NVR 5000 Series

- 8/16-CH Network Video Input
- Up to 2*10TB Storage & NAS 4K Decoding Capabilities
- Dual Stream Recording
- · AI VCA Management
- & POS Integration • Enterprise ANPR Management
- ANR



VMS/CMS/APP

Superior Video Management

you the high-efficient and all-in-one solution.

Milesight 4K H.265 NVR Series offers a robust system for diverse applications and empowers to configure and manage advanced IP surveillance systems with ease and extreme reliability. Based on cutting-edge technology, Milesight NVRs

feature great user-experience in video recording, live view and playback, bringing

IP1 IP2

4K H.265 Pro NVR 7000 Series

- 16/32-CH Network Video Input
- Up to 4*10TB Storage & NAS
- 4K Decoding Capabilities
- Dual Stream Recording
- Al VCA Management & POS Integration
- Enterprise ANPR Management
- Dual Lan Giga Network Ports
- · Multi-video Output · ANR/RAID/N+1 Hot Spare
- · Dual Lan Giga Network Ports Multi-video Output

 - ANR/RAID/N+1 Hot Spare

Enterprise ANPR Management

• 32/64-CH Network Video Input

Up to 8*10TB Storage & NAS

4K Decoding Capabilities

Dual Stream Recording

Al VCA Management

& POS Integration

MILESIGHT BACK-END SOLUTION



4K H.265 Mini PoE NVR 1000 Series

- 4*PoE Plug & Play
- 4/8-CH Network Video Input
- Up to 10TB Storage & NAS
- 4K Decoding Capabilities
- Dual Strean Recording
- Al VCA Management & POS Integration
- Thermal Design
- ANR



4K H.265 Mini PoE NVR 5000 Series

- 8*PoE Plug & Play • 8/16-CH Network Video Input
- Up to 2*10TB Storage & NAS
- 4K Decoding Capabilities
- Dual Stream Recording AI VCA Management &
- POS Integration
- Enterprise ANPR Management



4K H.265 Mini PoE NVR 7000 Series

- Up to 24*PoE Plug & Play
- 16/32-CH Network Video Input Up to 4*10TB Storage & NAS
- 4K Decoding Capabilities
- Dual Stream Recording
- AI VCA Management & POS Integration
- Multi-video Output
- ANR/RAID/N+1 Hot Spare
- Enterprise ANPR Management



16/32/64-CH 6Bay Enterprise NVR

- 16/32-CH Models Available,
- 64-CH Coming Soon
- Pre-loaded with Milesight VMS Enterprise
- Windows System
- Central Management for Single Site & Multiple Sites
- High Scalability
- Al & IoT Capabilities
- Ready-to-go Design for Easy Installation
- N+M Failover





























Manage Anytime with M-VMS Mobile



M-VMS Mobile

CMS



Milesight CMS

- · A central management system for Milesight cameras and Milesight NVRS
- Fully integrated with Milesight network cameras and NVRs Comprehensive management via IP/Domain, P2P and Milesight DDNS
- Support H.265/H.264 video compression
- Support multiple monitors (Up to 4 monitors, 64-CH for each monitor)
- Support up to 256 devices
- Support two-layer E-map Support Milesight VCA functions
- Support advanced functions like ANPR solution, Heat Map and Auto Tracking, etc.
- Support Crowd Management Solution

APP



M-Sight Pro APP

- · Simultaneously managing Milesight network cameras and NVRs Support Milesight Cloud Management
- Smooth and High Quality Live Streaming
- Support image capture/video recording functions File management Efficient Split Playback
- · Transcoding to get better playback performance Support scanning QR code to get a remote view via P2P
- Support iOS and Android handheld device
- · Support alarm video push notification





Milesight Smart Tools

- Unified management for network cameras and NVRs
- Batch settings for Milesight devices
- · Online batch upgrade for Milesight devices
- Fast, comprehensive and powerful calculation

Milesight AC CE **SSORIES** MAP

See the Unseen to Know **Indoor Air Quality**

IAQ Sensor









Smart Supermarket

Smart Hospital

AM107

2-in-1 AM102/AM102L

- Traffic light indicator
- Anti-theft protection
- Battery life up to 7 years (AM102) / 9 years (AM102L)
- Cost-effective bulk deployment



3-in-1

AM103/AM103L





- Traffic light status indicator
- Anti-theft protection
- Smart screen mode
- Hibernation mode
- Support data storage and retransmission
- 2.13 -inch E-ink screen (AM103)
- Vivid emoticon indication (AM103)
- Light/dark color theme (AM103)
- Multiple display styles (AM103)
- Battery life up to 3 years (AM103) / 4 years (AM103L)

















• 2.13 inch E-ink screen

7-in-1

- Visual and intuitive display
- Powered via USB Type-C
- Battery life up to 1 year

7/8/9-in-1

AM307(L)/AM308(L)/AM319(L)

- Traffic light indicator & buzzer
- Higher accuracy & Smart screen mode
- Anti-theft protection
- Data retrieval and data retransmission
- 4.2-inch E-ink screen (AM307/AM308/AM319)
- Vivid emoticon indication (AM307/AM308/AM319)
- Powered via USB Type-C(AM319/AM319L)
- Battery life up to 3 years (AM307) / 1 year (AM308)
- Battery life up to 4 years (AM307L) / 1.5 year (AM308L)





























VS121 Al Workplace Occupancy Sensor



- LoRaWAN® & PoE version
- High ceiling mount version (7 meters)
- Up to 98% accuracy
- 78 m² detection area
- 16 custom detection regions
- · Bi-directional people counting
- Smart U-turn detection
- Compliant with GDPR
- 100% Anonymous detection
- Support Milesight D2D featuring LoRa®

VS133 AI ToF People Counting Sensor

- LoRaWAN® & PoE version
- On-board Al algorithm
- 2ND generation ToF technology
- Up to 99.8% accuracy
- Staff detection
- Adults/children differentiation
- Compliant with GDPR
- 100% anonymous detection
- Bi-directional people counting
- Smart U-turn detection
- Support multi-device stitching



VS135 Ultra ToF People Counting Sensor



- Rated at IP65
- High ceiling mount version up to 6.5 meters high is available
- LoRaWAN® & PoE & Wi-Fi HaLow versions
- On-board AI algorithm
- 2ND generation ToF technology
- Up to 99.8% accuracy
- Staff detection
- Adults/children differentiation
- Compliant with GDPR
- Bi-directional people counting
- Smart U-turn detection
- Support multi-device stitching
- Advanced heat map available (VS135-P)

VS330 Cubicle Occupancy Sensor

- Combine PIR & ToF technology
- Up to 99.5% accuracy
- Operate in smart logic
- · Compliant with GDPR
- 100% anonymous detection
- Real-time data collection
- Low power consumption
- Conformal coating on PCBABattery life up to 4 years



VS340/VS341 Desk & Seat Occupancy Sensor



- LoRaWAN® wireless deployment
- Up to 98% accuracy
- 100% anonymous detection
- Adjustable detection angle
- Battery life up to 5 years
- Support Milesight D2D featuring LoRa®
- Combine highly sensitive PIR & Thermopile (VS341)

VS350 Passage People Counter

- Dual PIR sensors
- 100% GDPR compliance
- Built-in temperature sensing
- Battery life up to 4 years
- Support local storage of 1,000 historical records
- Anti-theft and over-temperature alarming reports
- Support Milesight D2D featuring LoRa®



Smart Heating and Cooling Controls

WT Series







WT101 Smart Radiator Thermostat


- LoRaWAN® based for wireless transmission
- Accurate temperature detection and calibration
- Up to 16 heating plans within 1 pre-set date period
- Support child lock to prevent tampering
- Open window detection for smart management
- Fully compatible valve adapters out of the box
- Support integration with BMS systems
- Easy configuration via NFC
- Support Freeze protection





Schools

Modern Buildings



WT201 Smart Thermostat

- LoRaWAN® based for wireless transmission
- 4.2 -inch LCD screen
- 64 independent local scheduling
- 4 customizable temperature control and 3 fan modes
- Compatible with hotel room card systems
- Support child lock to prevent tampering
- Support integration with BMS systems
- Easy configuration via NFC
- Support Milesight D2D featuring LoRa®



Modern Apartments



Building



WT30x Smart Fan Coil Thermostat

- LoRaWAN® based for wireless transmission
- 86mm hidden box and European 60mm round box available
- Applied in two pipes system, on/off relay or 0-10V valve control, and three-speed fan coil control
- Support pre-set date period with programmable schedules



Overall Features

- ► Industrial-grade Design
- Support Extra Temperature and Humidity Detection (Except UDL&TILT&MLD)
- Rated at IP67
- ▶ Battery Life up to 5 Years
- ▶ Easy Configuration via NFC



Smart Office



Smart Hotel

EM300-DI Pulse Counter

- Pulse/digital signals & temperature & humidity
- Great partner of old water meters
- IP67 rating for harsh environment
- Data retrieval and data retransmission





EM300-MCS Magnetic Contact Switch Sensor

- Detect the opening or closing event of door & window to ensure security
- Data retrieval and data retransmission

EM300-CL Capacitive Level Sensor

- Liquid level monitoring using non-contact capacitive sensing
- Reliable accuracy with strong anti-interference ability






EM300-TH Temperature & Humidity Sensor

- Temperature & humidity sensor
- ±0.3℃ high accuracy of temperature and ±3% RH of humidity
- Data retrieval and data retransmission

EM300-SLD/ZLD Leak Detection Sensor

- Detect water leakage based on the principle of liquid conduction (SLD: Spot leak detection ZLD: Zone leak detection)
- LoRaWAN® certified (EM300-SLD)
- · Data retrieval and data retransmission





EM300-MLD Membrane Leak Detection Sensor

- Accurate conductive liquids' leakage detection in a large area
- Support local data storage and data retransmission & retrievability

EM310-TILT Tilt Sensor

- 3-Axis accelerometer & built-in zero adjustment
- 36 customized trigger rules & rated at IP67
- NFC configuration & easy installation





EM310-UDL Ultrasonic Distance/Level Sensor

- Non-contact distance detection with 3-450 cm measurement range and short blind zone
- Detect device gesture with built-in 3-axis accelerometer sensor to monitor device tilt status

EM320-TH Temperature & Humidity Sensor

- ±0.2°C high accuracy of temperature and ±2% RH of humidity
- · Strong waterproof performance for harsh environments
- FDA-approved food contact material
- · Anti-theft and anti-slip pad design on back cover
- Data retrieval and data retransmission





EM320-TILT FDA Approved Tilt Sensor

- 3-Axis accelerometer & built-in zero adjustment
- 36 customized trigger rules & rated at IP67

Revolutionizing Measurement and Monitoring

EM400 Series Distance/Level Measurement Sensor



EM400-TLD ToF Laser Distance Sensor

- Detection ranges from 2 cm to 350 cm
- Designed for level monitoring in small trash bins
- Two pre-set modes: standard mode/ bin mode
- ToF Technology for high accuracy and almost no blind spot



Overall Features

- ▶ Rated at IP67
- ► LoRaWAN® & NB Version
- ► Embedded 3-Axis Accelerometer & NTC Thermistor
- ▶ Replaceable Battery Life up to 10 Years
- ▶ Easy Configuration via NFC





Smart Parking Lot



Boiler Expansion Monitoring



EM400-MUD Multifunctional Ultrasonic Distance Sensor

- Detection ranges from 3 cm to 450 cm
- Specialized in distance detection in trash bin and parking lot
- Pre-set modes: standard mode & bin mode
- Support pre-set parking lot mode (LoRaWAN® version only)
- Ultrasonic technology with small blind spots and support calibration

EM400-UDL Ultrasonic Distance Sensor

- Detection ranges from 25 cm to 1000 cm
- Professional for detecting water level in reservoir, industrial tank level and etc.
- Standard/professional versions available
- Support calibration for better accuracy





Reliable Data Collection for Long-term Remote Operation

EM500 Series - Outdoor Environment Monitoring Sensor

Overall Features

- ▶ Rated at IP67
- ▶ Replaceable Battery Life Up to 10 years
- ▶ Ultra-wide-distance Transmission
- ▶ NFC Configuration









EM500-CO₂ Carbon Dioxide Sensor (4 in 1)

- 4 in 1 (CO₂, temperature, humidity, barometric pressure)
- Measuring ranges (0 to 50°C): 400 ppm to 5000 ppm



EM500-LGT Light Sensor

- · Accurate detection of any light changes
- Measuring ranges from 0 to 100, 000 lux with high precision



EM500-PP Pipe Pressure Sensor

- Shock & vibration & corrosion resistant
- Measuring accuracy around ±0.5% FS to prevent leakage danger
- Temperature compensation for correcting temperature changes



EM500-PT100 Industrial Temperature Sensor

- Customizable temperature (-200 ~ 800°C)
- Terminal heads are available varing from the straight tube, armored, SMT, threaded, magnet



EM500-UDL Ultrasonic Distance /Level Sensor

- Suitable for measuring benign & chemical mediums
- Non-contact detection for any corrosive liquid chemicals or combustibles
- Measurements in very small containers or openings
- Measuring ranges: 0.3-5 m/0.5-10 m



EM500-SMTC Soil Moisture, Temperature and Electrical Conductivity Sensor

- Research-grade accuracy in multiple soil media
- Corrosion resistance & tough probe
- Rapid monitoring of growing conditions



EM500-SWL Submersible Water Level Sensor

- Submersible pressure sensor not affected by foam, wind, or rain
- Measuring medium: water (Customizable for oil and other non-corrosive media)
- Customizable measuring range up to 200 m





WS101 Smart Button

- Support multiple press actions
- Convenient size
- Built-in LED indicator & buzzer
- Support Milesight D2D Featuring LoRa®
- Battery life over 5 years



WS201 Smart Fill Level Monitoring Sensor

- Detection ranges from 1 cm to 55 cm
- Suitable for diverse toilet paper dispenser
- Accurate fill level monitoring with ToF technology
- Battery life up to 2 years



WS156 & WS136 Smart Scene Panel

- 100% wire-free
- Customizable display (WS156)
- Customizable stickers (WS136)
- Battery life up to 3 years
- Support Milesight D2D Featuring LoRa®
- LoRaWAN® certified (WS156)



WS202 PIR & Light Sensor

- Occupancy or motion detection
- Convenient size
- Built-in light sensor & PIR sensor
- Support Milesight D2D Featuring LoRa®
- Battery life up to 4 years



WS203 Motion & TH Sensor

- Flexible motion detection
- Adjustable detection angles
- Battery life up to 5 years
- Built-in temperature and humidity sensor
- Support local data storage and data retransmission & retrievability
- Support Milesight D2D featuring LoRa®



WS301 Magnetic Contact Switch Sensor

- 100% wire-free
- · Tamper detection
- Built-in LED indicator
- Battery life up to 5 years
- Support Milesight D2D Featuring LoRa®



WS302 Sound Level Sensor

- Peak and average sound level measurement
- Simple design for blending with any interiors
- NFC configuration & wire-free installation
- LED alarm indicator
- Battery life up to 4 years



WS303 Mini Leak Detection Sensor

- Water leak detection with 0.5 mm to trigger alert
- Immediate warning locally and remotely
- Battery life up to 5 years & IP67 rated
- Support Milesight D2D featuring LoRa®



WS50x Wall Switch

- Time-delay, schedule, remote and scene-based control
- 1/2-gang & multinational versions (AU, EU, UK & US)
- Power consumption statistics
- Multicast for remote control in bulk
- Support Milesight D2D Featuring LoRa®



WS51x Smart Wall Socket

- Easy remote and local control
- Customizable scheduling control
- Group control with multicast
- Support overload protection
- V-0 flame-retardant material
- Support Milesight D2D featuring LoRa®



WS523 Portable Socket

- Remote & time-based ON/OFF
- Power consumption measurement and collection
- Overload protection/alarm
- Support multicast



WS558 Smart Light Controller

- Control up to 8 lighting circuits
- Remote & time-based ON/OFF
- Power consumption measurement
- Support Milesight D2D Featuring LoRa®

Sense the Invisible Danger

GS Series





GS101 LoRaWAN® Gas Detector

- Methane (CH4) sensor
- Event trigger
- Built-in auto-test function
- Ultra safe gas alarm threshold
- 800 records historical data storing capacity
- 5-year long life expectancy

GS301 LoRaWAN® Bathroom Odor Detector

- Detect NH₃ & H₂S with high accuracy
- Traffic light indicator & buzzer
- Battery life up to 3 years
- Support Milesight D2D Featuring LoRa®



Integrate Connectivity and Applications in One

DS Series







DS3604 IoT E-ink Display

- 4.2 E-ink screen
- Three pigment ink system: red/white/black
- Customized templates in multiple modules
- Support over 150 languages
- Battery life up to 5 years
- Open API & LoRaWAN® Button







Office

Pastroom

Hospital

CT101/CT103 Smart Current Transformer

CT Series

- Powered by the circuit under test, no batteries required
- Non-intrusive and quick installation without damaging circuits or shutting down the power supply
- Support sampling frequencies up to 3.3khz
- Determines the general direction of energy consumption and automatically calculates cumulative ampere-hour values once per second



 15 26

Professional Temperature Monitoring TS Series L@RaWAN® N C

TS101 Insertion Temperature Sensor



- ±0.5°C detection accuracy
- Food-grade enclosure and probe
- IP67 rated & IK10 rated (transceiver)
- Support data storage and retransmission
- Battery life up to 10 years

TS30x LoRaWAN® Temperature Sensor

- Rated at IP65
- Compliance with HACCP and 21 CFR Part 11B
- · Optimized readability with LCD screen
- Efficient data export in PDF
- Support connection of PT100 temperature probe and door magnetic sensor



High Capacity, Long Endurance, Plug and Play

IP67 & 12000mAh UPS

UPS01 Uninterruptible Power Supply

- Capacity up to 12000mAh & IP67 rated
- Up to 32 hours' supplement
- Data Protection & Plug and Play



Accurate, Reliable and **Continuous Weather Monitoring**

WTS Series

L@RaWAN® N 🔿

Overall Features

- All-in-one IoT Weather Station
- Solar-powered & Chargeable Batteries Backup
- Robust and Rugged
- Various Application Scenarios
- Data Retrieval and Data Retransmission

















WTS305 **IoT Weather Station** Standard Version



WTS506 **IoT Weather Station** Pro Version

Protect and Manage Critical Assets at All Times











AT101 Outdoor Asset Tracker

- Highly-accurate GNSS positioning
- Cooperate with Wi-Fi positioning
- Support Geofencing
- Provide motion/periodic/timing Modes
- IP67 rated & IK09 rated

- Easy configuration via NFC or Bluetooth
- Embedded 3-Axis Accelerometer & NTC Thermistor
- Support data storage and retransmission
- Battery life over 15 years

iBox Kit Series

Milesight iBox Kit is designed for users to guickly evaluate the LoRaWAN® technology with testified devices and services. Going comprehensively digital transformation with more certainty, these solutions are the one step before users to scale connected device deployments securely with high











- Starters Enjoy It for Putting PoCs into Action with Reduced Time & Cost
- Operators Need It for New Projects and Potential Market Demands
- Deployers Love It for Easy to Deploy and Integrate with Multiple NS Platforms





Smart Restroom Solution

Occupancy Conditions

6

One Key Alarm

Emergency Response

Reshape Restroom, Release the Values of Smartness

VACANT

Milesight Smart Restroom Solution seamlessly integrates advanced operational and environmental sensors and IoT technologies breaking the limitations of traditional restrooms.

Air Quality

Usage Conditions

Queue Monitoring, Traffic Counting

Real-Time NH₃, H₂S, Temperature



- Effective Toilet Paper Replacement with Fill Level Monitoring
- Advanced HVAC Systems Based on H₂S and NH₃ **Detection Data**
- Detect Leaks Immediately with Leak Detection and Take Countermeasures.
- Integrated Information Displayed for Users Can Have a Visual View of the Restroom Conditions
- Metering Management in Real Time to Improve Energy Utilization and Energy Saving
- Occupancy Mastery Based on Cubicles Vacancy Data

Sensing to Get Advanced Imaging Insights



X1 Sensing Camera for Indoor Scenarios



- · Inspire sensing insights through images
- 2MP high-definition images
- · Easy-to-get wireless deployment
- Low power consumption
- Multi-object catching
- Multi-capturing modes
- Compact design
- · Powerful camera capacity
- Collaborate with AloT Sensing Platform
- Compatible with third-party platforms
- Battery life up to 2 years
- Wi-Fi HaLow version available


X5 Sensing Camera for Outdoor Applications

- 4G transmission
- Wi-Fi configuration
- · Active based on time, DI, PIR, radar, temperature or noise
- IP66 rated & Adjustable rain cover
- Support GPS
- 2MP high-definition images
- Support infrared supplement light without disturbance
- Wireless deployment
- Power supply via type-c and solar power
- Support hibernate mode
- Collaborate with AloT Sensing Platform
- · Compatible with third-party platforms



Milesight AloT Sensing Platform

The AloT sensing platform aims to form a data group of each sensing object including all aspects for further analysis to avoid the incomplete, unreliable problem because of scattered data.



Device Management

- Add Sensing Devices & Check the Latest Device Telemetry Data
- Customized ROI Realizing Image Subdivision
- Recognize the Image Information of Meters and Digital Display Instrument, Define Al Recognition Values

Sensing Objects

- Build a Sensing Object from Different Telemetry Data of Different Devices
- Search Historical Data of Sensing Objects

Trigger

- Low Battery and Inactive Status Trigger Alarm
 Duch
- Multiple HTTP and MQTT Receivers Can Be Set

(1)

Dashboard

- Real-Time Update of Images Captured by Sensing Cameras
- Statistics on Inactive and Active Device Status
- Device Exception Alarm (Low Battery or Inactive Status)

Open APIs

- Normalize All Data of The Sensing Object
- Support Data Output to Third-Party Platforms for Secondary Applications



- Batch Hardware Updating
- Configuration Files Batch Importing





UF51 5G CPE

- Flexible deployment
- Dual band Wi-Fi
- Outstanding performance
- Flexible installation
- Multiple industrial interfaces
- PoE PD powered



UF31 5G Dongle

- Plug & play dongle for 5G connectivity
- SA/NSA & super-fast5G speed
- Palm-sized design for any limited space
- Accelerator of 5G embedded applications

UR75 High-Performance 5G Industrial Router

- Fast speed 4G/5G network
- Wi-Fi 6
- Rich interfaces
- ① Gigabit Ethernet ports for lightning transmission of data
- ② 1 x RS232, 1 x RS485, 1 x DI, 1 x DO
- 3 4 x Wi-Fi, 4 x cellular, 1 x GPS
- 4 1 x USB port
- Industrial-grade design





UR32L Industrial Cellular Router

- High cost-effective with main router function
- 2 x 10/100 Mbps Ethernet interfaces for reliable network
- Support global 4G LTE network



UR35 Industrial Cellular Router

- Rich interfaces
- ① 4 x PoE PSE Ethernet ports
- ② 1 x RS232, 1 x RS485, 1 x DI, 1 x DO
- ③ Wi-Fi & GPS
- 4 FXS port for telephone communication
- Wide input voltage
- Support secondary development with Python SDK & API
- · Industrial-grade design



Rugged Communications for Mission

verizon/

UR32 Industrial Cellular Router

- Rich interfaces
- ① Wi-Fi/GPS (alternative)
- 2 PoE (optional)
- 3 2 x Ethernet ports, 1 x RS232, 1 x DI, 1 x DO
- Support secondary development with Python SDK & API
- Industrial-grade design
- Verizon Open Development Certification



UR41 Mini Industrial Router

- Itsy-bitsy router with great flexibility
- Rich interfaces
- ① GNSS
- ② 1 x RS232/RS485, 1 x DI, 1 x DO
- 3 1 x Ethernet port
- Ultra-low power consumption
- Industrial-grade design



PoE Switch

- Multiple-port options: 4, 8, 16, 24
- Smart PoE power supply
- Superb transmission
- Flexible extend mode
- SFP uplink port
- Surge protection

Bring Data Acquisition & Remote Control with Ease

IoT Controller





UC100 IoT Controller

- RS485 to LoRaWAN® transmission
- Cost-effective & super-tiny size
- Support Milesight D2D Featuring LoRa®



UC50x Series LoRaWAN® Controller

- Rich industrial interfaces: RS232/RS485(Switchable), GPIO, analog input and SDI-12
- Waterproof design including IP67 case and M12 connectors
- DC powered and built-in battery (optional)
- Solar powered (UC501)
- NFC or wired USB port for configuring
- Battery life up to 10 years
- Support internal antenna or external antenna version
- Multicast function and over threshold reporting are
- Support local data storage (600 pieces), retrievability and retransmission



UC300 IoT Controller

- Backhaul connectivity: LoRaWAN® technology
- Rich interfaces: DI/DO/AI/RS232/RS485/PT100 RTD input
- Customized trigger rules
- · Desk, wall & DIN mounting
- Support Milesight D2D Featuring LoRa®









UC51x Series LoRaWAN® Solenoid **Valve Controller**

- 2 x outputs for connecting DC latching solenoid
- Two GPIO interfaces for flow monitoring or valve status monitoring
- DC powered or solar powered (UC511)
- Time and flow control
- LoRaWAN® certified (UC512)
- Battery life up to 10 years
- Support internal antenna or external antenna
- Store locally 1000 historical records and support retransmission to prevent data loss

Remote Management Platform









Get the **Free Trial** now and begin your data-driven future.

Milesight IoT Cloud

Milesight IoT Cloud provides unparalleled levels of vertical integration with Milesight LoRaWAN® devices.

- Transform real-time and historical data into drag-and-drop widgets on dashboard
- Control access and monitor projects from anywhere
- Email and mobile push notifications based on triggered events
- Built on AWS to provide confidential and reliable infrastructure for your data
- Licensing with ease: just copy & paste and upgrade is done

DeviceHub



Milesight DeviceHub is a platform which is designed to provide a high-efficiency, low maintenance solution to easily deploy Milesight IoT devices (especially industrial cellular routers) across multiple locations, reducing complexity and increasing productivity.

- · Large scale deployment
- Real-time monitoring
- · Comprehensive report

Milesight VPN

Milesight VPN is a web-based VPN monitoring and management platform.

- Intuitive Web GUI
- · Connection status overview
- Easy to setup VPN tunnel
- Access to remote devices securely
- Support up to 1000+ connected devices

